

m o o o i

# Flock of Light

STUDIO TOER

Flock of Light is an (art) installation that is developed to be a lighting product in a size that fits your home. Inspired by the organic form and dynamism of a swarm of fireflies, Flock of Light mimicks a natural nocturnal phenomenon that will evoke sensations wherever it settles.



---

## *Flock of Light Flock of Light 11*

### *Dimensions*

80cm | 31.5"

65cm | 25.6"



65cm | 25.6"



### *Product*

**WIDTH** 80cm | 31.5"

**HEIGHT** 65cm | 25.6"

**DEPTH** 65cm | 25.6"

**WEIGHT NETTO** 0.9kg | 1.98lbs

---

### *Technical CE*

#### **MATERIAL**

Brass and bronze with plastic diffusers

**ENERGY LABEL**

Energy Label A+

**LIGHTSOURCE TYPE**

LED

**NUMBER OF LIGHTSOURCES**

11

**INPUT VOLTAGE**

220-240

**MAX POWER CONSUMPTION**

13W

**LAMPHOLDER**

LED (Solid state)

**CABLE LENGTH**

250cm | 98.4"

**COLOUR TEMPERATUE**

2700 K

**LIGHT DIRECTION**

All directions

**INSTALLATION REQUIRED**

Yes

**LIGHTSOURCE INCLUDED**

Yes

**SHAPE**

Abstract

**FREQUENCY**

50/60

**DIMMABLE**

Yes

**COLOUR**

Transparent with tinned cores

**CANOPY**

Pebble II White, ABS

**CRI**

91

**LIGHT OUTPUT**

1240 lm

---

*Technical cULus***MATERIAL**

Brass and bronze with plastic diffusers

**ENERGY LABEL**

Energy Label A+

**LIGHTSOURCE TYPE**

LED

**NUMBER OF LIGHTSOURCES**

11

**INPUT VOLTAGE**

110-130

**MAX POWER CONSUMPTION**

13W

**LAMPHOLDER**

LED (Solid state)

**CABLE LENGTH**

250cm | 98.4"

**COLOUR TEMPERATUE**

2700 K

**INSTALLATION REQUIRED**

Yes

**LIGHTSOURCE INCLUDED**

Yes

**SHAPE**

Abstract

**FREQUENCY**

50/60

**DIMMABLE**

Yes

**COLOUR**

Transparent with tinned cores

**CANOPY**

Pebble II White, ABS

**CRI**

91

**LIGHT DIRECTION**

All directions

**LIGHT OUTPUT**

1240 lm

*Flock of Light Flock of Light 21**Dimensions*

135cm | 53.2"

85cm | 33.5"

*Product***WIDTH** 135cm | 53.1"**HEIGHT** 65cm | 25.6"**DEPTH** 85cm | 33.5"**WEIGHT NETTO** 1.4kg | 3.09lbs*Technical CE***MATERIAL**

Brass and bronze with plastic diffusers

**ENERGY LABEL**

Energy Label A+

**LIGHTSOURCE TYPE**

LED

**NUMBER OF LIGHTSOURCES**

21

**INPUT VOLTAGE**

220-240

**MAX POWER CONSUMPTION**

23W

**LAMPHOLDER**

LED (Solid state)

**CABLE LENGTH**

250cm | 98.4"

**COLOUR TEMPERATURE**

2700 K

**LIGHT DIRECTION**

All directions

**INSTALLATION REQUIRED**

Yes

**LIGHTSOURCE INCLUDED**

Yes

**SHAPE**

Abstract

**FREQUENCY**

50/60

**DIMMABLE**

Yes

**COLOUR**

Transparent with tinned cores

**CANOPY**

Pebble II White, ABS

**CRI**

91

**LIGHT OUTPUT**

2308 lm

## Technical cULus

### MATERIAL

Brass and bronze with plastic diffusers

### ENERGY LABEL

Energy Label A+

### LIGHTSOURCE TYPE

LED

### NUMBER OF LIGHTSOURCES

21

### INPUT VOLTAGE

110-130

### MAX POWER CONSUMPTION

23W

### LAMPHOLDER

LED (Solid state)

### CABLE LENGTH

250cm | 98.4"

### COLOUR TEMPERATUE

2700 K

### LIGHT DIRECTION

All directions

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE INCLUDED

Yes

### SHAPE

Abstract

### FREQUENCY

50/60

### DIMMABLE

Yes

### COLOUR

Transparent with tinned cores

### CANOPY

Pebble II White, ABS

### CRI

91

### LIGHT OUTPUT

2308 lm

---

## Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

### DIMMER TYPE

Mains dimmable (trailing edge / reverse phase)

### LOAD TYPE

Capacitive load (C-Type)

---